



# Actinic BL TL-D(K) Secura – additional safety and HACCP approval

## Actinic BL TL-D(K) Secura

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL-D(K) Secura lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. In addition, they have a special "Secura" sleeve that keeps all glass and components together in the case of accidental breakage. This eliminates the risk of glass splinters showering down on food preparation areas, for example. And that is why it meets the strict HACCP requirements. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice.

### Benefits

- Perfectly matches the eye sensitivity of houseflies and in this way attracts more insects
- Safe for use
- Good environmental choice
- No risk of glass particles

### Features

- Emits long-wave UV-A radiation in the 350-400nm range
- UV-B/UV-A ratio less than 0.1 % (UV-B 280-315nm)
- 100% lead-free
- Low mercury content
- Shatterproof sleeve

# Actinic BL TL-D(K) Secura

## Application

- Insect traps, Electronic Fly Killers (EFKs)

## Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


## Versions



TL-D (K) Secura

TL-D Secura

## Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-DK Secura 36W/10 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

General Information	
Cap-Base	G13
Main Application	Insect traps
Light Technical	
Colour Code	10
Colour Designation	Actinic
Mechanical and Housing	
Bulb Shape	T26
UV	
UV-B/UV-A (IEC)	0.2 %

## Approval and Application

## Actinic BL TL-D(K) Secura

Order Code	Full Product Name	Mercury (Hg) Content (Nom)
928019801003	Actinic BL TL-DK Secura 36W/10 1SL/25	8.0 mg

Order Code	Full Product Name	Mercury (Hg) Content (Nom)
928024701029	Actinic BL TL-D 15W/10 Secura 1SL/25	5.5 mg

### Operating and Electrical

Order Code	Full Product Name	Lamp		Power
		Current (Nom)	Voltage (Nom)	(Rated) (Nom)
928019801003	Actinic BL TL-DK Secura 36W/10 1SL/25	0.865 A	50 V	36 W

Order Code	Full Product Name	Lamp		Power
		Current (Nom)	Voltage (Nom)	(Rated) (Nom)
928024701029	Actinic BL TL-D 15W/10 Secura 1SL/25	0.335 A	55 V	15 W

### General Information

Order Code	Full Product Name	Life To 50%	Useful Life
		Failures (Nom)	(Nom)
928019801003	Actinic BL TL-DK Secura 36W/10 1SL/25	9000 h	5000 h

Order Code	Full Product Name	Life To 50%	Useful Life
		Failures (Nom)	(Nom)
928024701029	Actinic BL TL-D 15W/10 Secura 1SL/25	8000 h	9000 h

### UV

Order Code	Full Product Name	UV-A Radiation 100Hr (IEC)
928019801003	Actinic BL TL-DK Secura 36W/10 1SL/25	8.8 W

Order Code	Full Product Name	UV-A Radiation 100Hr (IEC)
928024701029	Actinic BL TL-D 15W/10 Secura 1SL/25	3.15 W

