



GreenPerform Direct LED Panel

RC099V G2 LED38/840 PSU W30L120

Polystyrene bowl/cover prismatic

The GreenPerform RC099V G2 direct panel is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600 x 600, 300 x 1,200, and 600 x 1,200 mm with max: 110 lm/w system efficacy. Its UGR19 version brings more visual comfort in the office. By means of its compact design, the housing height (without driver) reaches only 35 mm which gives more flexibility for recessed installation.

Product data

General Information		Controls and Dimming	
Lamp colour code	840 neutral white	Dimmable	No
Optical cover/lens type	Polystyrene bowl/cover prismatic	Mechanical and Housing	
Control interface	-	Housing material	Steel
Protection class IEC	Safety class II (II)	Optical cover/lens material	Polystyrene
CE mark	CE mark	Optical cover/lens finish	Opal
Number of products on MCB (16 A type B)	24	Overall length	1195 mm
Light source engine type	LED	Overall width	295 mm
Operating and Electrical		Overall height	57 mm
Input Voltage	220 to 240 V	Colour	White RAL 9003
Input frequency	50 or 60 Hz	Approval and Application	
Power factor (min.)	0.9	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	-

GreenPerform Direct LED Panel

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	3800 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>80
Initial input power	35 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Product Data

Full product code	692382864380599
Order product name	RC099V G2 LED38/840 PSU W30L120
EAN/UPC – product	6923828643805
Order code	911401700763
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	911401700763
SAP net weight (piece)	2.100 kg



Dimensional drawing



SmartBright Panel RC099V

