



Product Description

MASTER PL-L 4 Pin

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 2 parallel fluorescent tubes

Benefits

- Optimal light performance for short or long operation per switch on
- Long life and sustainable light output

Features

- 4-pin base without starter and capacitor
- Lamp characteristics are influenced by operating conditions and control gear used
- Lamp performance is governed by temperature of the coolest spot
- Dimming is possible

Application

- Designed for general lighting in shops, offices, hotels and specific task lighting, as well as outdoors in residential areas and parks

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


MASTER PL-L 4 Pin

Versions



24 W 2G11

Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L 55W/840/4P 1CT/25	39.0 mm	18.0 mm	509.2 mm	535 mm	541.6 mm
MASTER PL-L 24W/840/4P 1CT/25	39.0 mm	18.0 mm	289.2 mm	315 mm	321.6 mm

MASTER PL-L 4 Pin

Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	2.0 mg

Controls and Dimming

Dimmable	Yes
----------	-----

General Information

Cap-Base	2G11
Life To 50% Failures Preheat (Nom)	20000 h
LSF Preheat 16000 h Rated	82 %
LSF Preheat 20000 h Rated	50 %
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	98 %
LSF Preheat 8000 h Rated	97 %

Light Technical

Colour Code	840
Colour Designation	Cool White (CW)
Correlated Colour Temperature (Nom)	4000 K
Colour Rendering Index (Nom)	82
LLMF 16000 h Rated	90 %
LLMF 20000 h Rated	90 %

Temperature

Design Temperature (Nom)	30 °C
--------------------------	-------

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
927903208470	MASTER PL-L 24W/840/4P 1CT/25	26 kWh
927908708470	MASTER PL-L 55W/840/4P 1CT/25	61 kWh

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927903208470	MASTER PL-L 24W/840/4P 1CT/25	0.345 A	24.0 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927908708470	MASTER PL-L 55W/840/4P 1CT/25	0.525 A	55.0 W

General Information (1/2)

Order Code	Full Product Name	Life To 10% Failures (Nom)	Life To 50% Failures (Nom)	LSF 12000 h Rated	LSF 2000 h Rated
927903208470	MASTER PL-L 24W/840/4P 1CT/25	10000 h	15000 h	80 %	99 %

Order Code	Full Product Name	Life To 10% Failures (Nom)	Life To 50% Failures (Nom)	LSF 12000 h Rated	LSF 2000 h Rated
927908708470	MASTER PL-L 55W/840/4P 1CT/25	-	-	-	-

General Information (2/2)

Order Code	Full Product Name	LSF 4000 h Rated	LSF 6000 h Rated	LSF 8000 h Rated	System Description
927903208470	MASTER PL-L 24W/840/4P 1CT/25	98 %	96 %	94 %	na

Order Code	Full Product Name	LSF 4000 h Rated	LSF 6000 h Rated	LSF 8000 h Rated	System Description
927908708470	MASTER PL-L 55W/840/4P 1CT/25	-	-	-	High Frequency

Light Technical (1/2)

MASTER PL-L 4 Pin

Order Code	Full Product Name	LLMF	LLMF	LLMF	LLMF
		12000 h	2000 h	4000 h	6000 h
		Rated	Rated	Rated	Rated
927903208470	MASTER PL-L 24W/840/4P 1CT/25	90 %	94 %	93 %	92 %

Order Code	Full Product Name	LLMF	LLMF	LLMF	LLMF
		12000 h	2000 h	4000 h	6000 h
		Rated	Rated	Rated	Rated
927908708470	MASTER PL-L 55W/840/4P 1CT/25	91 %	95 %	94 %	93 %

Light Technical (2/2)

Order Code	Full Product Name	LLMF	Luminous	Luminous	Luminous
		8000 h	Efficacy	Luminous	Flux (Rated)
		Rated	(rated) (Nom)	Flux (Nom)	(Nom)
927903208470	MASTER PL-L 24W/840/4P 1CT/25	91 %	75 lm/W	1800 lm	1800 lm

Order Code	Full Product Name	LLMF	Luminous	Luminous	Luminous
		8000 h	Efficacy	Luminous	Flux (Rated)
		Rated	(rated) (Nom)	Flux (Nom)	(Nom)
927908708470	MASTER PL-L 55W/840/4P 1CT/25	92 %	87 lm/W	4800 lm	4800 lm

