



MASTER TL5 High Output

MASTER TL5 HO 54W/840 1SL/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap base	G5 [G5]	Lamp Luminous Efficacy EM (Nom)	83 lm/W
Life to 50% failures preheat (nom.)	30000 h	Colour Rendering Index,horiz (Max)	85
Features	na [Not Applicable]	Colour Rendering Index,horiz (Min)	80
System description	High Output (HO)	Colour Rendering Index,horiz (Nom)	85
LSF preheat 2,000 hours rated	99 %	LLMF 2000 h Rated	96 %
LSF preheat 4,000 hours rated	99 %	LLMF 4000 h Rated	95 %
LSF preheat 6,000 hours rated	99 %	LLMF 6000 h Rated	94 %
LSF preheat 8,000 hours rated	99 %	LLMF 8000 h Rated	93 %
LSF preheat 16,000 hours rated	97 %	LLMF 12000 h Rated	92 %
LSF preheat 20,000 hours rated	84 %	LLMF 16000 h Rated	91 %
		LLMF 20000 h Rated	90 %
Light Technical		Temperature	
Colour Code	840 [CCT of 4,000 K]	Design temperature (nom.)	35 °C
Lamp Luminous Flux 25°C EL (Nom)	5000 lm		
Lamp Luminous Flux (Nom)	4500 lm		
Colour Designation	Cool White (CW)		
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	93 lm/W		
Colour Temperature, horizontal (Nom)	4000 K		

MASTER TL5 High Output

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Cap-base information	Green Plate
----------------------	-------------

Approval and Application


Energy efficiency label (EEL)	A+
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	59 kWh

Product Data

Full product code	871150064318655
-------------------	-----------------

Order product name	MASTER TL5 HO 54W/840 SLV/40
EAN/UPC – product	8711500643186
Order code	64318655
Local order code	9279-290-84055
SAP numerator – quantity per pack	1
Numerator – packs per outer box	40
SAP material	927929084055
SAP net weight (piece)	105.800 g
ILCOS code	FDH-54/40/1B-L/P-G5-16/1150



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 54W/840 SLV/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm

TL5 HO 54W/840

Photometric data



Lightcolour /840

Lightcolour /840

MASTER TL5 High Output

Lifetime



LDLE_TL5-HO8_0001-Life expectancy diagram

LDLE_TL5-HO8_0002-Life expectancy diagram



LDLM_TL5-HO8_0001-Lumen maintenance diagram

