



Ecofit Ledtubes T8

ECOFIT LEDtube 1200mm 16W 765 T8 CT G WV

Upgrade to efficient, long-lasting LED tubes with the Ecofit LED tubes. Ecofit LED tubes are a fast and easy way to replace your old fluorescent tubes with modern, efficient LED technology. Good quality of light with a natural lighting effect for use in general lighting applications with low initial investment – an environmentally friendly solution.

Product data


General Information		Starting time (nom.)	
Cap base	G13 [Medium Bi-Pin Fluorescent]		0.5 s
EU RoHS compliant	Yes	Warm-up time to 60% light (nom.)	0.5 s
Nominal lifetime (nom.)	15000 h	Power factor (nom.)	0.48
Switching cycle	50,000X	Voltage (Nom)	100-240 V
Light Technical		Temperature	
Colour Code	765 [CCT of 6,500 K]	T-ambient (max.)	45 °C
Technical Beam Angle (Nom)	240 °	T-ambient (min.)	-20 °C
Lamp Luminous Flux 25°C EL (Nom)	1600 lm	T storage (max.)	65 °C
Colour Designation	Cool Daylight	T storage (min.)	-40 °C
Colour Temperature, horizontal (Nom)	6500 K	T-Case maximum (nom.)	70 °C
Lamp Luminous Efficacy EM (Nom)	100.00 lm/W	Controls and Dimming	
Colour consistency	<7	Dimmable	No
Colour Rendering Index,horiz (Nom)	70	Mechanical and Housing	
LLMF at end of nominal lifetime (nom.)	70 %	Product length	1200 mm
Operating and Electrical		Approval and Application	
Input frequency	50 to 60 Hz	Energy efficiency label (EEL)	Not applicable
Power (Rated) (Nom)	16 W	Energy-saving product	Yes
Lamp current (max.)	264 mA	Approval marks	RoHS compliance KEMA Keur certificate
Lamp current (min.)	143 mA		

Ecofit Ledtubes T8

Energy consumption kWh/1,000 hours	- kWh
Product Data	
Full product code	871869962458300
Order product name	ECOFIT LEDtube 1200mm 16W 765 T8 CT G WV
EAN/UPC – product	8718699624583
Order code	929001979412

Numerator – quantity per pack	1
Numerator – packs per outer box	20
SAP material	929001979412
SAP net weight (piece)	0.215 kg


Dimensional drawing




TLED 1200mm T8 110-220 16W 1600lm 6500K

Product	D1	D2	A1	A2	A3
ECOFIT LEDtube 1200mm 16W 765 T8 CT G WV	25.7 mm	28 mm	1198 mm	1205 mm	1212 mm


Photometric data



LEDtube G13 6500K 16W





LEDtube G13



LEDtube G13 6500K 16W



Ecofit Ledtubes T8

Lifetime




LEDtube G13 LifetimeVsTc

LEDtube G13



LEDtube G13

LEDtube G13 FailureRate



LEDtube G13 LumenVsTc

Ecofit Ledtubes T8

